

QFN-10 CSP-8

TPS62300, TPS62301, TPS62302 TPS62303, TPS62304, TPS62305 TPS62311, TPS62313, TPS62320, TPS62321

SLVS528C-JULY 2004-REVISED DECEMBER 2005

500-mA, 3-MHz SYNCHRONOUS STEP-DOWN CONVERTER IN CHIP SCALE PACKAGING

FEATURES

- Up to 93% Efficiency at 3-MHz Operation
- Up to 500-mA Output Current at $V_1 = 2.7 V$
- 3-MHz Fixed Frequency Operation
- Best in Class Load and Line Transient
- Complete 1-mm Component Profile Solution
- -0.5% / +1.3% PWM DC Voltage Accuracy Over Temperature
- 35-ns Minimum On-Time
- Power-Save Mode Operation at Light Load Currents
- Fixed and Adjustable Output Voltage
- Only 86-µA Quiescent Current
- 100% Duty Cycle for Lowest Dropout
- Synchronizable *On the Fly* to External Clock Signal
- Integrated Active Power-Down Sequencing (TPS6232x only)
- Available in a 10-Pin QFN (3 x 3 mm) and Highly Reliable 8-Pin NanoFree[™] and NanoStar[™] (CSP) Packaging

APPLICATIONS

- Cell Phones, Smart-Phones
- WLAN and Bluetooth[™] Applications
- Micro DC-DC Converter Modules
- PDAs, Pocket PCs
- USB-Based DSL Modems
- Digital Cameras

ÆÀ



Figure 1. Smallest Solution Size Application (Fixed Output Voltage)

DESCRIPTION

The TPS623xx device is a high-frequency synchronous step-down dc-dc converter optimized for battery-powered portable applications. Intended for low-power applications, the TPS623xx supports up to 500-mA load current and allows the use of tiny, low cost chip inductor and capacitors.

The device is ideal for mobile phones and similar portable applications powered by a single-cell Li-Ion battery or by 3-cell NiMH/NiCd batteries. With an output voltage range from 5.4 V down to 0.6 V, the device supports the low-voltage TMS320[™] DSP family, processors in smart-phones, PDAs as well as notebooks, and handheld computers.

The TPS62300 operates at 3-MHz fixed switching frequency and enters the power-save mode operation at light load currents to maintain high efficiency over the entire load current range. For low noise applications, the device can be forced into fixed frequency PWM mode by pulling the MODE/SYNC pin high. The device can also be synchronized to an external clock signal in the range of 3 MHz. In the shutdown mode, the current consumption is reduced to less than 1 μ A.

The TPS623xx is available in a 10-pin leadless package (3 x 3 mm QFN) and an 8-pin chip-scale package (CSP).



Figure 2. Efficiency vs Load Current

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

NanoFree, NanoStar, TMS320 are trademarks of Texas Instruments. Bluetooth is a trademark of Bluetooth SIG, Inc.

PowerPAD is a trademark of Texas Instsruments.

SLVS528C-JULY 2004-REVISED DECEMBER 2005



T _A	PART NUMBER	OUTPUT VOLTAGE	UNDERVOLTAGE LOCKOUT	PACKAGE	ORDERING ⁽¹⁾⁽²⁾	PACKAGE MARKING
	TRECOOD	Adjustable	2.4 V	QFN-10	TPS62300DRC	AMN
	19562300	Adjustable	2.4 V	CSP-8 (lead-free)	TPS62300YZD	N/A
	TD000004	4.5.1/	2.4 V	QFN-10	TPS62301DRC	AMO
	19302301	1.5 V	2.4 V	CSP-8 (lead-free)	TPS62301YZD	N/A
	TRECOOD	1.6.1/	2.4 V	QFN-10	TPS62302DRC	AMQ
	1P362302	1.6 V	2.4 V	CSP-8 (lead-free)	TPS62302YZD	N/A
	TDOCODO	1.0.1/	2.4 V	QFN-10	TPS62303DRC	AMR
	1P362303	1.6 V	2.4 V	CSP-8 (lead-free)	TPS62303YZD	N/A
	TPS62304	1.2 V	2.4 V	QFN-10	TPS62304DRC	AMS
40°C to 95°C			2.4 V	CSP-8 (lead-free)	TPS62304YZD	N/A
-40°C 10 85°C	TRECODE	1.875 V	2.4 V	QFN-10	TPS62305DRC	ANU
	1F302305		2.4 V	CSP-8 (lead-free)	TPS62305YZD	N/A
	TPS62311	1.5 V	2 V	CSP-8 (lead-free)	TPS62311YZD	N/A
	TPS62313	1.8 V	2 V	CSP-8 (lead-free)	TPS62313YZD	N/A
			2.4 V	QFN-10	TPS62320DRC	AMX
	TPS62320	Adjustable	2.4 V	CSP-8 (lead-free)	TPS62320YZD	N/A
			2.4 V	CSP-8	TPS62320YED	N/A
			2.4 V	QFN-10	TPS62321DRC	AMY
	TPS62321	1.5 V	2.4 V	CSP-8 (lead-free)	TPS62321YZD	N/A
			2.4 V	CSP-8	TPS62321YED	N/A

ORDERING INFORMATION

(1) The YZD and YED packages are available in tape and reel. Add a R suffix (TPS62300YxDR) to order quantities of 3000 parts. Add a T suffix (TPS62300YxDT) to order quantities of 250 parts. The DRC package is available in tape and reel. Add a R suffix (TPS62300DRCR) to order quantities of 3000 parts.

(2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at www.ti.com.

ABSOLUTE MAXIMUM RATINGS

over operating free-air temperature range (unless otherwise noted)⁽¹⁾

		UNIT
	Voltage at VIN, AVIN ⁽²⁾	-0.3 V to 7 V
	Voltage at SW ⁽²⁾	-0.3 V to 7 V
VI	Voltage at FB, ADJ	-0.3V to 3.6 V
	Voltage at EN, MODE/SYNC (2)	-0.3 V to V _I + 0.3 V
	Voltage at VOUT ⁽²⁾	0.3 V to 5.4 V
Ι _Ο	Continuous output current	500 mA
	Power dissipation	Internally limited
T _A	Operating temperature range	-40°C to 85°C
T _J (max)	Maximum operating junction temperature	150°C
T _{stg}	Storage temperature range	-65°C to 150°C

(1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) All voltage values are with respect to network ground terminal.

DISSIPATION RATINGS⁽¹⁾

PACKAGE	$R_{ heta JA}$	POWER RATING FOR T _A ≤ 25°C	DERATING FACTOR ABOVE T _A = 25°C		
DRC	49°C/W	2050 mW	21 mW/°C		
YZD	250°C/W	400 mW	4 mW/°C		
YED	250°C/W	400 mW	4 mW/°C		

(1) Maximum power dissipation is a function of $T_J(max)$, θ_{JA} and T_A . The maximum allowable power dissipation at any allowable ambient temperature is $P_D = [T_J(max)-T_A] / \theta_{JA}$

ELECTRICAL CHARACTERISTICS

 $V_1 = 3.6 \text{ V}$, $V_0 = 1.6 \text{ V}$, $EN = V_1$, MODE/SYNC = GND, L = 1 μ H, $C_0 = 10 \mu$ F, $T_A = -40^{\circ}$ C to 85°C, typical values are at $T_A = 25^{\circ}$ C (unless otherwise noted)

PARAMETER			TEST CONDITIONS	MIN	TYP	MAX	UNIT
SUPPLY CUR	RENT						
VI	Input voltage range			2.7		6	V
		TPS6230x TPS6232x	I _O = 0 mA. PFM mode enabled, device not switching		86	105	μΑ
la	Operating quiescent	TPS6231x	$I_{O} = 0$ mA. PFM mode enabled, device not switching		86	120	μA
IQ	current	TPS6230x TPS6231x TPS6232x	I _O = 0 mA. Switching with no load (MODE/SYNC = VIN)		3.6		mA
I _(SD)	Shutdown current		EN = GND		0.1	1	μΑ
	Undervoltage	TPS6230x TPS6232x			2.40	2.55	V
()	lockout threshold	TPS6231x			2.00	2.20	V
ENABLE, MO	DE/SYNC						
V _(EN)	EN high-level input voltage			1.2			V
V(MODE/SYNC)	MODE/SYNC high-level input voltage			1.3			V
V _(EN) , V _(MODE/SYNC)	EN, MODE/SYNC low-level input voltage					0.4	V
I _(EN) , I _(MODE/SYNC)	EN, MODE/SYNC input leakage current		EN, MODE/SYNC = GND or VIN		0.01	1	μΑ
POWER SWIT	СН						
-		registeres	$V_{I} = V_{(GS)} = 3.6 V$		420	750	mΩ
DS(on)	F-CHAINER MUSFET UN RESISTATICE		$V_{I} = V_{(GS)} = 2.8 V$		520	1000	mΩ
I _{lkg(PMOS)}	P-channel leakage cur	rent	V _(DS) = 6 V			1	μΑ
r		rocistanco	$V_{\rm I} = V_{\rm (GS)} = 3.6 \rm V$		330	750	mΩ
DS(on)		Tresistance	$V_{I} = V_{(GS)} = 2.8 V$		400	1000	mΩ
R _(DIS)	Discharge resistor for p sequence (TPS6232x	oower-down only)			30	50	Ω
I _{lkg(NMOS)}	N-channel leakage cur	rent	V _(DS) = 6 V			1	μΑ
	P-MOS current limit		$2.7 \text{ V} \leq \text{V}_{\text{I}} \leq 6 \text{ V}$	670	780	890	mA
	N-MOS current limit - s	sourcing	$2.7 \ V \leq V_l \leq 6 \ V$	550	720	890	mA
	N-MOS current limit - s	sinking	$2.7~V \leq V_{I} \leq 6~V$	-460	-600	-740	mA
	Input current limit unde conditions	er short-circuit	$V_0 = 0 V$		390		mA
	Thermal shutdown				150		°C
	Thermal shutdown hysteresis				20		°C

SLVS528C-JULY 2004-REVISED DECEMBER 2005



ELECTRICAL CHARACTERISTICS (continued)

 V_I = 3.6 V, V_O = 1.6 V, EN = V_I , MODE/SYNC = GND, L = 1 μ H, C_O = 10 μ F, T_A = -40°C to 85°C, typical values are at T_A = 25°C (unless otherwise noted)

PARAMETER			TEST CON	MIN	TYP	MAX	UNIT	
OSCILLATOR								
f _{SW}	Oscillator frequency				2.65	3	3.35	MHz
f _(SYNC)	Synchronization range				2.65		3.35	MHz
	Duty cycle of external of	clock signal			20%		80%	
OUTPUT								
Vo	Adjustable output voltage range	TPS62300 TPS62320		0.6		5.4	V	
V _(FB)	Regulated feedback voltage	TPS62300 TPS62320				0.4		V
A _(PT)	DC power train amplific (V _O /V _(ADJ))	ation			1.496	1.5	1.504	
t _{on(MIN)}	Minimum on-time (P-ch MOSFET)	annel				35		ns
	Resistance into VOUT	sense pin			700	1000		kΩ
	Resistance into ADJ pi	n	V _(FB) > 0.4 V		700	1000	1300	kΩ
I _(FB)	Feedback input bias current	TPS62300 TPS62320	V _(FB) = 0.4 V		1		nA	
	Adjustable output voltage ⁽¹⁾	TPS62300 TPS62320			-2%		+2%	
	Fixed output voltage	TPS6230x TPS6231x TPS6232x	2.7 V \leq V _I \leq 6 V, 0 mA \leq I _{O(D} PFM/PWM mode operation	-2%		+2%		
		TPS62304			-2%		+2.5%	
		TPS62305		-2%		+2.7%		
.,	Adjustable output	TPS62300 TPS62320		$T_A = 25^{\circ}C$	-0.5%		+1.3%	
vo	voltage dc accuracy ⁽¹⁾			$-40^\circ C \leq T_A \leq 85^\circ C$	-0.5%		+1.3%	
		TPS6230x		$T_A = 25^{\circ}C$	-0.5%		+1.3%	
		TPS6232x	PWM mode operation,	$-40^\circ C \leq T_A \leq 85^\circ C$	-0.5%		+1.3%	
	Fixed output voltage	TDS62204	V _I = 3.6 V, No Load	$T_A = 25^{\circ}C$	-0.5%		+1.8%	
	dc accuracy	1F 302304		$-40^\circ C \leq T_A \leq 85^\circ C$	-0.5%		+1.8%	
		TPS62305		T _A = 25°C	-0.3%		+1.7%	
				$-40^\circ C \leq T_A \leq 85^\circ C$	-0.5%		+2%	
	DC output voltage load	regulation	$I_0 = 0$ mA to 500 mA, MODE	$V/SYNC = V_1$		-0.001	-0.002	%/mA
	DC output voltage load (power train in direct dr	regulation ive mode)	$V_{(ADJ)}$ externally forced to 1.0 $I_0 = 0$ mA to 500 mA, MODE	067 V, /SYNC = V _I		-0.0003	-0.0006	%/mA
	DC output voltage line	regulation	$V_{I} = V_{O} + 0.5 V (min 2.7 V) to6 V, I_{O} = 100 mA, MODE/SY$	D NC = V _I		0.11	0.2	%/V
	DC output voltage line regulation (power train in direct drive mode)		$V_{(ADJ)}$ externally forced to 1.0 $V_1 = V_0 + 0.5 V$ (min 2.7 V) to MODE/SYNC = V_1		0.035	0.1	%/V	
	Integrator slew rate						200	μV/μs
ΔV_O	Power-save mode rippl	e voltage	$I_0 = 1 \text{ mA}, \text{ MODE/SYNC} = G$	GND		0.025 V _O		V _{P-P}
	Start-up time		$I_0 = 200 \text{ mA}$, Time from activ	ve EN to V _O		250		μs
lu cous	Leakage current into S	W pin	$V_{I} > V_{O}, \ 0 \ V \leq V_{(SW)} \leq VIN, \ E$	N = GND		0.1	1	ıιΔ
·ikg(SVV)	Reverse leakage curre	nt into SW pin	$V_{I} = open, V_{(SW)} = 6 V, EN =$	GND		0.1	1	μ

(1) Output voltage specification for the adjustable version does not include tolerance of external voltage programming resistors.

SW

VOUT

MODE/SYNC

PGND

C

AGND

GND

SW

VOUT

MODE/SYNC

Т

1

1

Ы

(A1)

(B1)

C1

(D1)

SLVS528C-JULY 2004-REVISED DECEMBER 2005



PIN ASSIGNMENTS

TERMINAL FUNCTIONS

TERMINAL									
NAME	NO. QFN	NO. CSP	I/O	DESCRIPTION					
VIN	1	A2	I	Supply voltage for output power stage.					
AVIN	2		Ι	This is the input voltage pin of the device. Connect directly to the input bypass capacitor.					
EN	3	B2	I	This is the enable pin of the device. Connecting this pin to ground forces the device into shutdown mode. Pulling this pin to V_1 enables the device. This pin must not be left floating and must be terminated.					
ADJ	4	C2	I/O	This is the internal reference voltage used to regulate V ₀ . This pin is not connected on fixed output voltage version of TPS6230xDRC and TPS6232xDRC. Do not connect ADJ pin on fixed output voltage version of TPS6230xYZD, TPS6231xYZD and TPS6232xYxD.					
				On TPS62300 and TPS62320, this pin can also be used as an external control input. The output voltage is 1.5x the applied voltage at ADJ.					
FB	5	D2	I	This is the feedback pin of the device. For the adjustable version, an external resistor divider is connected to this pin. The internal voltage divider is disabled for the adjustable version. This pin is not connected on fixed output voltage version of TPS6230xDRC and TPS6232xDRC. Do not connect the FB pin on the fixed output voltage version of TPS6230xYZD, TPS6231xYZD and TPS6232xYxD.					
VOUT	6	D1	Ι	Output feedback sense input. Connect VOUT to the converter's output.					
AGND	7			Analog ground. Connect to PGND via the PowerPAD [™] underneath IC.					
				Input for synchronization to external clock signal. This pin must not be left floating and must be terminated. Synchronizes the converter switching frequency to an external clock signal					
MODE/SYNC	8	C1	I	MODE/SYNC = LOW (GND): The device is operating in fixed frequency pulse width modulation mode (PWM) at high-load currents and in pulse frequency modulation mode (PFM) at light load currents.					
				MODE/SYNC = HIGH (VIN): Low-noise mode enabled, fixed frequency PWM operation forced.					
PGND	9	A1		Power ground.					
SW	10	B1	I/O	This is the switch pin of the converter and is connected to the drain of the internal Power MOSFETs.					
PowerPAD™			N/A	Internally connected to PGND.					

SLVS528C-JULY 2004-REVISED DECEMBER 2005



FUNCTIONAL BLOCK DIAGRAM



NOTE A: For the adjustable versions (TPS62300 and TPS62320) the internal feedback divider is disabled.

PARAMETER MEASUREMENT INFORMATION



List of Components: U1 = TPS6230x L1 = FDK MIPW3226 Series C1, C2 = X5R/X7R



SLVS528C-JULY 2004-REVISED DECEMBER 2005

TYPICAL CHARACTERISTICS

Table of Graphs

			FIGURE
η	Efficiency	vs Load current	3, 4, 5, 6
	Enciency	vs Input voltage	7
	Line transient response		8
	Load transient response		9, 10, 11, 12, 13, 14, 15, 16
Vo	DC output voltage	vs Load current	17
V _{FB}	Regulated feedback voltage	vs Temperature	18
l _Q	No load quiescent current	vs Input voltage	19
f _s	Switching frequency	vs Temperature	20
	Duty cycle jitter		21
-	P-channel MOSFET r _{DS(on)}	vs Input voltage	22
DS(on)	N-channel MOSFET r _{DS(on)}	vs Input voltage	23
	PWM operation		24
	Power-save mode operation		25
	Dynamic voltage management		26, 27
	Start-up		28, 29
	Power down (TPS6232x)		30









SLVS528C-JULY 2004-REVISED DECEMBER 2005









SLVS528C-JULY 2004-REVISED DECEMBER 2005

TYPICAL CHARACTERISTICS (continued)



9

SLVS528C-JULY 2004-REVISED DECEMBER 2005



TYPICAL CHARACTERISTICS (continued)

l₀ = 50 mA or 200 mA/div



Figure 13.





PWM OPERATION $V_1 = 3.6 V,$ $V_0 = 1.6 V$ MODE/SYNC = HIGH $L = 0.9 \mu$ H, $C_0 = 4.7 \mu$ F

LOAD TRANSIENT RESPONSE IN



t - Time - 2 μs/div

Figure 14.

LOAD TRANSIENT RESPONSE IN PFM OPERATION



SLVS528C-JULY 2004-REVISED DECEMBER 2005





SLVS528C-JULY 2004-REVISED DECEMBER 2005



TYPICAL CHARACTERISTICS (continued)



DUTY CYCLE JITTER







PWM OPERATION



Figure 24.



SLVS528C-JULY 2004-REVISED DECEMBER 2005

TYPICAL CHARACTERISTICS (continued)



 $R_L = 5 \Omega$ L = 0.9 μ H, C_O = 10 μ F, MODE/SYNC = HIGH

t - Time - 20 µs/div

_

Figure 27.



t – Time – 20 µs/div



START-UP



Figure 28.

SLVS528C-JULY 2004-REVISED DECEMBER 2005



DETAILED DESCRIPTION

OPERATION

The TPS6230x, TPS6231x, and TPS6232x are synchronous step-down converters typically operating with a 3-MHz fixed frequency pulse width modulation (PWM) at moderate to heavy load currents. At light load currents, the converter operates in power-save mode with pulse frequency modulation (PFM). The operating frequency is set to 3 MHz and can be synchronized *on-the-fly* to an external oscillator.

During PWM operation, the converter uses a unique fast response, voltage mode, controller scheme with input voltage feed-forward. This achieves *best-in-class* load and line response and allows the use of tiny inductors and small ceramic input and output capacitors. At the beginning of each switching cycle, the P-channel MOSFET switch is turned on and the inductor current ramps up until the comparator trips and the control logic turns off the switch.

The device integrates two current limits, one in the P-channel MOSFET and another one in the N-channel MOSFET. When the current in the P-channel MOSFET reaches its current limit, the P-channel MOSFET is turned off and the N-channel MOSFET is turned on. When the current in the N-channel MOSFET is above the N-MOS current limit threshold, the N-channel MOSFET remains on until the current drops below its current limit. The current limit in the N-channel MOSFET is important for small duty-cycle operation when the current in the inductor does not decrease because of the P-channel MOSFET current limit delay, or because of start-up conditions where the output voltage is low.

TYPICAL CHARACTERISTICS (continued)

♥ Texas Instruments

www.ti.com



DETAILED DESCRIPTION (continued)

POWER-SAVE MODE

With decreasing load current, the device automatically switches into pulse skipping operation in which the power stage operates intermittently based on load demand. By running cycles periodically, the switching losses are minimized, and the device runs with a minimum quiescent current and maintaining high efficiency.

In power-save mode, the converter only operates when the output voltage trips below a set threshold voltage (-1.5% $V_{O(NOMINAL)}$). It ramps up the output voltage with several pulses and goes into power-save mode once the output voltage exceeds the nominal output voltage. As a consequence, the average output voltage is slightly lower than its nominal value in the power-save mode operation.

The output current at which the PFM/PWM transition occurs is approximated by Equation 1:

$$I_{\text{PFM/PWM}} = \frac{V_{\text{O}}}{V_{\text{I}}} \times \frac{V_{\text{I}} - V_{\text{O}}}{2 \times L \times f_{\text{SW}}}$$

• I_{PEM/PWM} : output current at which PFM/PWM transition occurs

- f_{SW} : switching frequency (3-MHz typical)
- L : inductor value



Figure 31. Power-Save Mode Threshold

MODE SELECTION AND FREQUENCY SYNCHRONIZATION

The MODE/SYNC pin is a multipurpose pin which allows mode selection and frequency synchronization. Connecting this pin to GND enables the automatic PWM and power-save mode operation. The converter operates in fixed frequency PWM mode at moderate to heavy loads and in the PFM mode during light loads, which maintains high efficiency over a wide load current range.

Pulling the MODE/SYNC pin high forces the converter to operate in the PWM mode even at light load currents. The advantage is that the converter operates with a fixed frequency that allows simple filtering of the switching frequency for noise-sensitive applications. In this mode, the efficiency is lower compared to the power-save mode during light loads. For additional flexibility, it is possible to switch from power-save mode to forced PWM mode during operation. This allows efficient power management by adjusting the operation of the converter to the specific system requirements.

The TPS6230x, TPS6231x, and TPS6232x can also be synchronized to an external 3-MHz clock signal by the MODE/SYNC pin. During synchronization, the mode is set to fixed-frequency operation and the P-channel MOSFET turnon is synchronized to the falling edge of the external clock. This creates the ability for multiple converters to be connected together in a master-slave configuration for frequency matching of the converters (see the application section for more details, Figure 37).

SOFT START

The TPS6230x, TPS6231x, and TPS6232x have an internal soft-start circuit that limits the inrush current during start-up. This prevents possible input voltage drops when a battery or a high-impedance power source is connected to the input of the converter. The soft start is implemented as a digital circuit increasing the switch current in steps of typically 195 mA, 390 mA, 585 mA, and the typical switch current limit of 780 mA. Therefore, the start-up time mainly depends on the output capacitor and load current.

(1)



DETAILED DESCRIPTION (continued)

LOW-DROPOUT OPERATION 100% DUTY CYCLE

In 100% duty cycle mode, the TPS6230x, TPS6231x, and TPS6232x offer a low input-to-output voltage difference. In this mode, the P-channel MOSFET is constantly turned on. This is particularly useful in battery-powered applications to achieve the longest operation time by taking full advantage of the whole battery voltage range. The minimum input voltage to maintain regulation, depending on the load current and output voltage, can be calculated as:

- $V_{I(MIN)} = V_{O(MAX)} + I_{O(MAX)} \times (r_{DS(on) MAX} + R_L)$
- I_{O(MAX)} : Maximum output current
- r_{DS(on) MAX} : Maximum P-channel switch r_{DS(on)}
- R_L : DC resistance of the inductor
- V_{O(MAX)} : nominal output voltage plus maximum output voltage tolerance

ENABLE

The device starts operation when EN is set high and starts up with the soft start as previously described.

Pulling the EN pin low forces the device into shutdown, with a shutdown quiescent current of typically 0.1 µA. In this mode, the P and N-channel MOSFETs are turned off, the internal resistor feedback divider is disconnected, and the entire internal-control circuitry is switched off. When an output voltage is present during shutdown mode, which can be caused by an external voltage source or super capacitor, the reverse leakage is specified under electrical characteristics. For proper operation, the EN pin must be terminated and must not be left floating.

In addition, the TPS6232x devices integrate a resistor, typically 35 Ω , to actively discharge the output capacitor when the device turns off. The required time to discharge the output capacitor at V_O depends on load current.

UNDERVOLTAGE LOCKOUT

The undervoltage lockout circuit prevents the device from misoperation at low input voltages. It prevents the converter from turning on the switch or rectifier MOSFET under undefined conditions.

The TPS6231x devices have a UVLO threshold set to 2 V (typical). Fully functional operation is permitted down to 2.4 V input voltage. EN is set low for input voltages lower than 2.4 V to avoid the possibility of misoperation.

TPS6231x devices are to be considered where the user requires direct control of the turn-off sequence as part of a larger power management system.

SHORT-CIRCUIT PROTECTION

As soon as the output voltage falls below 50% of the nominal output voltage, the converter current limit is reduced by 50% of the nominal value. Because the short-circuit protection is enabled during start-up, the device does not deliver more than half of its nominal current limit until the output voltage exceeds 50% of the nominal output voltage. This needs to be considered when a load acting as a current sink is connected to the output of the converter.

THERMAL SHUTDOWN

As soon as the junction temperature, T_J, exceeds typically 150°C, the device goes into thermal shutdown. In this mode, the P- and N-channel MOSFETs are turned off. The device continues its operation when the junction temperature falls below typically 130°C again.

APPLICATION INFORMATION

ADJUSTABLE OUTPUT VOLTAGE

When the adjustable output voltage versions, TPS62300 or TPS62320, are used, the output voltage is set by the external resistor divider (see Figure 32).

The output voltage is calculated as:

$$V_{O} = 1.5 \times V_{ref} \times \left(1 + \frac{R1}{R2}\right)$$
 with an internal reference voltage V_{ref} typical = 0.4 V (2)

To keep the operating quiescent current to a minimum, it is recommended that R2 be set in the range of 75 k Ω to 130 k Ω . Route the FB line away from noise sources, such as the inductor or the SW line.



Figure 32. Adjustable Output Voltage Version

OUTPUT FILTER DESIGN (INDUCTOR AND OUTPUT CAPACITOR)

The TPS6230x, TPS6231x, and TPS6232x series of step-down converters have internal loop compensation. Therefore, the external L-C filter must be selected to work with the internal compensation.

The device has been designed to operate with inductance values between a minimum of 0.7 μ H and maximum of 6.2 μ H. The internal compensation is optimized to operate with an output filter of L = 1 μ H and C_O = 10 μ F. Such an output filter has its corner frequency at:

$$f_{\rm C} = \frac{1}{2\pi \sqrt{\rm L \times C_{\rm O}}} = \frac{1}{2\pi \sqrt{1 \ \mu \rm H \times 10 \ \mu \rm F}} = 50.3 \ \rm kHz$$
(3)

Operation with a higher corner frequency (e.g., L = 1 μ H, C₀ = 4.7 μ F) is possible. However, it is recommended the loop stability be checked in detail. Selecting a larger output capacitor value (e.g., 22 μ F) is less critical because the corner frequency moves to lower frequencies with fewer stability problems. The possible output filter combinations are listed in Table 1.

Regardless of the inductance value, operation is recommended with 10- μ F output capacitor in applications with high-load transients (e.g., \geq 1600 mA/ μ s).

INDUCTANCE (L)	OUTPUT CAPACITANCE (C _O)
1 μΗ	\ge 4.7 µF (ceramic capacitor)
2.2 μΗ	\ge 2.2 μ F (ceramic capacitor)

The inductor value also has an impact on the pulse skipping operation. The transition into power-save mode begins when the valley inductor current goes below a level set internally. Lower inductor values result in higher ripple current which occurs at lower load currents. This results in a dip in efficiency at light load operations.

SLVS528C-JULY 2004-REVISED DECEMBER 2005

INDUCTOR SELECTION

Even though the inductor does not influence the operating frequency, the inductor value has a direct effect on the ripple current. The selected inductor has to be rated for its dc resistance and saturation current. The inductor ripple current (ΔI_L) decreases with higher inductance and increases with higher V_I or V_O.

$$\Delta I_{L} = \frac{V_{O}}{V_{I}} \times \frac{V_{I} - V_{O}}{L \times f_{SW}} \qquad \qquad \Delta I_{L(MAX)} = I_{O(MAX)} + \frac{\Delta I_{L}}{2}$$
(4)

' Texas truments

www.ti.com

with: f_{SW} = switching frequency (3 MHz typical)

L = inductor value

 ΔI_{L} = peak-to-peak inductor ripple current

 $I_{L(MAX)}$ = maximum inductor current

Normally, it is advisable to operate with a ripple of less than 30% of the average output current. Accepting larger values of ripple current allows the use of low inductances, but results in higher output voltage ripple, greater core losses, and lower output current capability.

The total losses of the coil consist of both the losses in the DC resistance $(R_{(DC)})$ and the following frequency-dependent components:

- The losses in the core material (magnetic hysteresis loss, especially at high switching frequencies)
- Additional losses in the conductor from the skin effect (current displacement at high frequencies)
- Magnetic field losses of the neighboring windings (proximity effect)
- Radiation losses

The following inductor series from different suppliers have been used with the TPS6230x, TPS6231x, and TPS6232x converters.

MANUFACTURER	SERIES	DIMENSIONS		
FDK	MIPW3226	3.2 x 2.6 x 1 = 8.32 mm ³		
	LQ CB2016	2 x 1.6 x 1.6 = 5.12 mm ³		
Taiyo Yuden	LQ CB2012	2 x 1.2 x 1.2 = 2.88 mm ³		
	LQ CBL2012	2 x 1.2 x 1 = 2.40 mm ³		
TDK	VLF3010AT	2.8 x 2.6 x 1 = 7.28 mm ³		
Wuerth Elektronik	WE-TPC XS	3.3 x 3.5 x 0.95 = 10.97 mm ³		
Coilcraft	LPS3010	3.3 x 3.3 x 1 = 10.89 mm ³		
JFE	32R1560	$3.2 \times 2.5 \times 0.6 = 4.8 \text{ mm}^3$		

Table 2. List of Inductors

OUTPUT CAPACITOR SELECTION

The advanced fast-response voltage mode control scheme of the TPS6230x, TPS6231x, and TPS6232x allows the use of tiny ceramic capacitors. Ceramic capacitors with low ESR values have the lowest output voltage ripple and are recommended. The output capacitor requires either an X7R or X5R dielectric. Y5V and Z5U dielectric capacitors, aside from their wide variation in capacitance over temperature, become resistive at high frequencies.

At nominal load current, the device operates in PWM mode and the overall output voltage ripple is the sum of the voltage spike caused by the output capacitor ESR plus the voltage ripple caused by charging and discharging the output capacitor:

$$\Delta V_{O} = \frac{V_{O}}{V_{I}} \times \frac{V_{I} - V_{O}}{L \times f_{SW}} \times \left(\frac{1}{8 \times C_{O} \times f_{SW}} + ESR\right), \text{ maximum for high } V_{I}$$
(5)

At light loads, the device operates in power-save mode and the output voltage ripple is independent of the output capacitor value. The output voltage ripple is set by the internal comparator thresholds and propagation delays. The typical output voltage ripple is 1.5% of the nominal output voltage V_o.

INPUT CAPACITOR SELECTION

Because of the nature of the buck converter having a pulsating input current, a low ESR input capacitor is required to prevent large voltage transients that can cause misbehavior of the device or interferences with other circuits in the system. For most applications, a 2.2- μ F or 4.7- μ F capacitor is sufficient.

Take care when using only ceramic input capacitors. When a ceramic capacitor is used at the input and the power is being supplied through long wires, such as from a wall adapter, a load step at the output can induce ringing at the VIN pin. This ringing can couple to the output and be mistaken as loop instability or could even damage the part.

CHECKING LOOP STABILITY

The first step of circuit and stability evaluation is to look from a steady-state perspective at the following signals:

- Switching node, SW
- Inductor current, I_L
- Output ripple voltage, V_{O(AC)}

These are the basic signals that need to be measured when evaluating a switching converter. When the switching waveform shows large duty cycle jitter or the output voltage or inductor current shows oscillations, the regulation loop may be unstable. This is often a result of board layout and/or L-C combination.

As a next step in the evaluation of the regulation loop, the load transient response is tested. The time between the application of the load transient and the turn on of the P-channel MOSFET, the output capacitor must supply all of the current required by the load. V_O immediately shifts by an amount equal to $\Delta I_{(LOAD)} \times ESR$, where ESR is the effective series resistance of C_O. $\Delta I_{(LOAD)}$ begins to charge or discharge C_O generating a feedback error signal used by the regulator to return V_O to its steady-state value.

During this recovery time, V_0 can be monitored for settling time, overshoot or ringing that helps judge the converter's stability. Without any ringing, the loop has usually more than 45° of phase margin.

Because the damping factor of the circuitry is directly related to several resistive parameters (e.g., MOSFET $r_{DS(on)}$) that are temperature dependant, the loop stability analysis has to be done over the input voltage range, load current range, and temperature range.

PROGRAMMING THE OUTPUT VOLTAGE WITH A DAC

On TPS62300 and TPS62320 devices, the output voltage can be dynamically programmed to any voltage between 0.6 V and V_I (or 5.4 V whichever is lower) with an external DAC driving the ADJ and FB pins (see Figure 33). The output voltage is then equal to $A_{(PT)} \times V_{(DAC)}$ with a *Power Train* amplification $A_{(PT)}$ typical = 1.5.

When the output voltage is driven low, the converter reduces its output quickly in forced PWM mode, boosting the output energy back to the input. If the input is not connected to a low-impedance source capable of absorbing the energy, the input voltage can rise above the absolute maximum voltage of the part and get damaged. The faster V_0 is commanded low, the higher is the voltage spike at the input.

For best results, ramp the ADJ/FB signal as slow as the application allows. To avoid over-slew of the regulation loop of the converter, avoid abrupt changes in output voltage of > 300 mV/ μ s (depending on V₁, output voltage step size and L/C combination). If ramp control is unavailable, an RC filter can be inserted between the DAC output and ADJ/FB pins to slow down the control signal.



Figure 33. Filtering the DAC Voltage

SLVS528C-JULY 2004-REVISED DECEMBER 2005

LAYOUT CONSIDERATIONS

As for all switching power supplies, the layout is an important step in the design. High-speed operation of the TPS6230x, TPS6231x, and TPS6232x devices demand careful attention to PCB layout. Care must be taken in board layout to get the specified performance. If the layout is not carefully done, the regulator could show poor line and/or load regulation, stability issues as well as EMI problems. It is critical to provide a low inductance, impedance ground path. Therefore, use wide and short traces for the main current paths as indicated in bold on Figure 34.

The input capacitor should be placed as close as possible to the IC pins as well as the inductor and output capacitor. Use a common ground node for power ground and a different one for control ground (AGND) to minimize the effects of ground noise. Connect these ground nodes together (star point) underneath the IC and make sure that small signal components returning to the AGND pin do not share the high current path of C1 and C2.

The output voltage sense line (VOUT) should be connected right to the output capacitor and routed away from noisy components and traces (e.g., SW line). Its trace should be minimized and shielded by a guard-ring connected to the reference ground. The voltage setting resistive divider should be placed as close as possible to the AGND pin of the IC.



Figure 34. Layout Diagram



Figure 35. Suggested QFN Layout (Top)



Figure 36. Suggested QFN Layout (Bottom)

THERMAL INFORMATION

Implementation of integrated circuits in low-profile and fine-pitch surface-mount packages typically requires special attention to power dissipation. Many system-dependant issues such as thermal coupling, airflow, added heat sinks, and convection surfaces, and the presence of other heat-generating components, affect the power-dissipation limits of a given component

Three basic approaches for enhancing thermal performance are listed below:

- Improving the power dissipation capability of the PCB design
- Improving the thermal coupling of the component to the PCB
- Introducing airflow in the system

The maximum recommended junction temperature (T_J) of the TPS6230x, TPS6231x, and TPS6232x devices is 125°C. The thermal resistance of the 8-pin CSP package (YZD and YED) is $R_{\theta JA} = 250°C/W$. Specified regulator operation is assured to a maximum ambient temperature T_A of 85°C. Therefore, the maximum power dissipation is about 160 mW. More power can be dissipated if the maximum ambient temperature of the application is lower or if the PowerPADTM package (DRC) is used.

$$P_{D(MAX)} = \frac{T_{J(MAX)} - T_{A}}{R_{\theta JA}} = \frac{125^{\circ}C - 85^{\circ}C}{250^{\circ}C/W} = 160 \text{ mW}$$

(6)

CHIP SCALE PACKAGE DIMENSIONS

The TPS6230x, TPS6231x, and TPS6232x are also available in an 8-bump chip scale package (YZD, NanoFree[™] and YED, NanoStar[™]). The package dimensions are given as:

- D = 1.970 ±0.05 mm
- E = 0.970 ±0.05 mm

SLVS528C-JULY 2004-REVISED DECEMBER 2005

APPLICATION EXAMPLES



Ch3: SW (1.2-V Output), Ch4: IL2

ij.

Texas

INSTRUMENTS www.ti.com

List of Components: L1, L2 = Taiyo Yuden LQ CB2016 C_{IN}, C1, C2, = X5R/X7R Ceramic Capacitor

PFM/PWM Automatic Switch High: Synchronized Operation

Forced 3 MHz Fixed Frequency Operation







Ch3: Inductor Current: IL1 Ch3: EN - External Control Signal

Figure 38. Speed-Up Circuitry for Fast Turnon Time

SLVS528C-JULY 2004-REVISED DECEMBER 2005



 C_1 , C_1 , = X5R/X7R Ceramic Capacitor

Figure 39. Dynamic Voltage Management Using I²C I/F

12-Jan-2006



TEXAS INSTRUMENTS www.ti.com

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Packag Qty	e Eco Plan ⁽²⁾	Lead/Ball Finish	n MSL Peak Temp ⁽³⁾
TPS62300DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62300DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62300YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62300YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62301DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62301DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62301YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62301YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62302DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62302DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62302YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62302YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62303DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62303DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62303YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62303YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62304DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62304DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62304YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62304YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62305DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62305DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62305YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62305YZDT	PREVIEW	DSBGA	YZD	8	250	TBD	Call TI	Call TI
TPS62311YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	e Eco Plan ⁽²⁾	Lead/Ball Finish	n MSL Peak Temp ⁽³⁾
TPS62311YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62313YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62313YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62320DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62320DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62320YEDR	ACTIVE	XCEPT	YED	8	3000	TBD	SNAGCU	Level-1-240C-UNLIM
TPS62320YEDT	ACTIVE	XCEPT	YED	8	250	TBD	SNAGCU	Level-1-240C-UNLIM
TPS62320YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62320YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62321DRCR	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62321DRCRG4	ACTIVE	SON	DRC	10	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-2-260C-1 YEAR
TPS62321YEDR	ACTIVE	XCEPT	YED	8	3000	TBD	SNAGCU	Level-1-240C-UNLIM
TPS62321YEDT	ACTIVE	XCEPT	YED	8	250	TBD	SNAGCU	Level-1-240C-UNLIM
TPS62321YZDR	ACTIVE	DSBGA	YZD	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM
TPS62321YZDT	ACTIVE	DSBGA	YZD	8	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details. **TBD**: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited



12-Jan-2006

information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

MECHANICAL DATA



NOTES: A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.

- B. This drawing is subject to change without notice.
- C. Small Outline No-Lead (SON) package configuration.
- The package thermal pad must be soldered to the board for thermal and mechanical performance. See the Product Data Sheet for details regarding the exposed thermal pad dimensions.
- $\not \stackrel{\frown}{\boxplus}$ Metalized features are supplier options and may not be on the package.





THERMAL PAD MECHANICAL DATA

DRC (S-PDSO-N10)

THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to a ground or power plane (whichever is applicable), or alternatively, a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, Quad Flatpack No-Lead Logic Packages, Texas Instruments Literature No. SCBA017. This document is available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.



Bottom View

NOTE: All linear dimensions are in millimeters

Exposed Thermal Pad Dimensions

DRC (S-PDSO-N10)



NOTES: A. All linear dimensions are in millimeters.

- B. This drawing is subject to change without notice.
- C. Publication IPC-7351 is recommended for alternate designs.
- D. This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, Quad Flat-Pack Packages, Texas Instruments Literature No. SCBA017, SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at www.ti.com http://www.ti.com.
- E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
- F. Customers should contact their board fabrication site for minimum solder mask web tolerances between signal pads.



YED (R-XBGA-N8)

DIE-SIZE BALL GRID ARRAY



- B. This drawing is subject to change without notice.
- C. NanoStar™ package configuration.
- Devices in YED package can have dimension D ranging from 1.85 to 2.65 mm and dimension E ranging from 0.85 to 1.65 mm.
 To determine the exact package size of a particular device, refer to the device datasheet or contact a local TI representative.
 Reference Product Data Sheet for array population.
 - 4 x 2 matrix pattern is shown for illustration only.
- F. This package contains tin-lead (SnPb) balls.
 Refer to YZD (Drawing #4205057) for lead-free balls.

NanoStar is a trademark of Texas Instruments.



YZD (R-XBGA-N8)

DIE-SIZE BALL GRID ARRAY



- B. This drawing is subject to change without notice.
- C. NanoFree™ package configuration.
- Devices in YZD package can have dimension D ranging from 1.85 to 2.65 mm and dimension E ranging from 0.85 to 1.65 mm.
 To determine the exact package size of a particular device, refer to the device datasheet or contact a local TI representative.
 Reference Product Data Sheet for array population.
- 4 x 2 matrix pattern is shown for illustration only.
- F. This package contains lead-free balls.
- Refer to YED (Drawing #4204180) for tin-lead (SnPb) balls.

NanoFree is a trademark of Texas Instruments.



IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments

Post Office Box 655303 Dallas, Texas 75265

Copyright © 2006, Texas Instruments Incorporated