



SYMBOL	MILLIMETERS			NOTE
	MIN.	NOM.	MAX.	
A	$\cancel{\text{---}}$	1.40	1.70	2
A <sub>1</sub>	0.50	0.60	$\cancel{\text{---}}$	
A <sub>2</sub>	0.60	$\cancel{\text{---}}$	1.10	
A <sub>3</sub>	0.20	$\cancel{\text{---}}$	$\cancel{\text{---}}$	
D/E	35.00 BSC			
D <sub>1</sub> /E <sub>1</sub>	31.75 REF.			
e	1.27 BSC			
$\phi_b$	0.60	0.75	0.90	
aaa	$\cancel{\text{---}}$	$\cancel{\text{---}}$	0.20	
bbb	$\cancel{\text{---}}$	$\cancel{\text{---}}$	0.25	
ccc	$\cancel{\text{---}}$	$\cancel{\text{---}}$	0.15	
ddd	$\cancel{\text{---}}$	$\cancel{\text{---}}$	0.30	
M	26			
REF.	JEDEC MO-192-BAR-2			

### NOTES:

- ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5M-1994
- SYMBOL "M" IS THE PIN MATRIX SIZE.
- LAND PAD OPENING – SOLDER MASK DEFINED  $\phi 0.615\text{mm}$  (0.024")
- HEAT SINK PULLBACK – 0.375mm MAX.

## 352-BALL METAL BGA (BG352) – CAVITY DOWN