



SYMBOL	DIMENSION IN INCHES								
	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX
A	.155	.172	.190	.155	.172	.190	.155	.172	.190
A1	.090	---	.120	.090	---	.120	.090	---	.120
B	.026	.028	.032	.026	.028	.032	.026	.028	.032
b1	.017	.019	.022	.017	.019	.022	.017	.019	.022
c	.006	.007	.012	.006	.007	.012	.006	.007	.012
D/E	.685	.690	.695	.985	.990	.995	1.185	1.190	1.195
D1/E1	.630	.650	.665	.930	.950	.965	1.130	1.150	1.165
D2/E2	.290	.305	.320	.440	.455	.470	.540	.555	.570
D3/E3	.500 REF.			.800 REF.			1.000 REF.		
e	.050 BSC			.050 BSC			.050 BSC		
N	44			68			84		
W	∅.350			∅.390 REF.			.450 SQ. REF.		
REF.	JEDEC MO-087-AB			JEDEC MO-087-AD			JEDEC MO-087-AE		

NOTES:

1. ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5M-1982.
2. LEAD WIDTH DIMENSION INCLUDE LEAD TRIM OFFSET and LEAD FINISH, LEAD FINISH: (HOT SOLDER DIP)
3. SYMBOL 'N' IS THE NUMBER OF TERMINALS.
4. SYMBOL 'W' IS THE DIMENSION OF THE EPROM WINDOW.
5. THESE PACKAGES MEET DIMENSIONAL REQUIREMENTS JEDEC MO-087.

44, 68, and 84-PIN WINDOWED CLCC (WC44, 68 and 84)