



SYMBOL	CB100			CB164		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	\pm	\pm	.135	\pm	\pm	.130
A1	\pm	\pm	.115	\pm	\pm	.110
A2	\pm	\pm	.020	\pm	\pm	.020
B	.006	.008	.012	.006	.008	.012
C	.005	.006	.009	.005	.006	.009
D1/E1	.740	.750	.765	1.120	1.130	1.145
D2/E2	.600 REF.			1.000 REF.		
F	.425	.450	.475	.175	.200	.225
H	2.300 BSC			2.300 BSC		
J	.030	.035	.040	.030	.035	.040
K	\pm	\pm	.020	\pm	\pm	.020
L	\pm	\pm	2.580	\pm	\pm	2.580
L1	2.490	2.500	2.510	2.485	2.500	2.505
L2	1.480	1.500	1.520	1.480	1.500	1.520
N	100			164		

NOTE:

1. ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5M-1982.
2. SYMBOL 'N' IS THE NUMBER OF TERMINALS.
3. PACKAGES ARE SHIPPED UNFORMED.
4. LEAD FINISH: GOLD (50 MICROINCHES MINIMUM) OVER NICKEL PER MIL-I-38535
5. PIN NUMBER SEQUENCE CLOCKWISE WHEN VIEW FROM NON LID SIDE.

100, 164-PIN CERAMIC BRAZED CQFP (CB100, CB164)
(XC3000 VERSION)