



| SYMBOL                         | MILLIMETERS |          |      |
|--------------------------------|-------------|----------|------|
|                                | MIN.        | NOM.     | MAX. |
| A                              | <i>h</i>    | 2.25     | 2.60 |
| A <sub>1</sub>                 | 0.40        | 0.50     | 0.60 |
| D/E                            | 27.00 BSC   |          |      |
| D <sub>1</sub> /E <sub>1</sub> | 2500 REF    |          |      |
| e                              | 1.00 BSC    |          |      |
| φ <sub>b</sub>                 | 0.50        | 0.60     | 0.70 |
| aaa                            | <i>h</i>    | <i>h</i> | 0.20 |
| ccc                            | <i>h</i>    | <i>h</i> | 0.35 |
| ddd                            | <i>h</i>    | <i>h</i> | 0.30 |
| eee                            | <i>h</i>    | <i>h</i> | 0.10 |
| M                              | 26          |          |      |

### NOTES:

1. ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5M-1994
2. SYMBOL 'M' IS THE BALL MATRIX SIZE.
3. CONFORMS TO JEDEC MO-151 AAL-1 (DEPOPULATED)

## 600-BALL FINE PITCH BGA (FG600)